



	IP Proprietary Telephones						Digital Proprietary Telephones		
	KX-NT560	KX-NT556	KX-NT553	KX-NT551	KX-NT546	KX-NT543	KX-DT521	KX-DT543	KX-DT546
Main LCD Display (Lines/Characters)	6 / 24	6 / 24	3 / 24	1 / 16	6 / 24	3 / 24	1 / 16	3 / 24	6 / 24
LCD Backlight	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Flexible CO Keys	4 x 8	3 x 12	2 x 12	8	24	24	8	24	24
Self-Labeling	Yes	Yes	Yes	-	-	-	-	-	-
Navigator Keys	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Soft Keys	4	4	4	-	4	4	-	4	4
Call Log Incoming/Outgoing Calls	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes
Auto Redial	Yes	Yes	Yes	Yes	Yes	Yes	-	Yes	Yes
Ethernet Port	2-Port (GbE)	2-Port (GbE)	2-Port (GbE)	2-Port (GbE)	2-Port	2-Port	-	-	-
Power over Ethernet (PoE)	Yes	Yes	Yes	Yes	Yes	Yes	-	-	-
AC Adaptor	Option	Option	Option	Option	Option	Option	-	-	-
Eco Mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes	-	-
Speakerphone	Yes (Full Duplex)	Yes (Full Duplex)	Yes (Full Duplex)	Yes (Full Duplex)	Yes	Yes	Yes (Full Duplex)	Yes (Full Duplex)	Yes (Full Duplex)
Headset Port	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Electric Hook Switch (EHS)	Yes	Yes	Yes	-	Yes	Yes	-	Yes	Yes
Built-in Bluetooth®	Yes	-	-	-	-	-	-	-	-
Wall Mountable	Option	Option	Option	Option	Option	Option	Option	Option	Option

Options										
Add-on 48-Key Module	KX-NT505	-	Yes	Yes	-	-	-	-	-	-
Digital DSS console	KX-DT590	-	-	-	-	-	-	Yes	Yes	Yes
Wall Mount Kit	KX-A433	Yes	Yes	Yes	-	Yes	Yes	-	Yes	Yes
	KX-A432	-	-	-	Yes	-	-	Yes	-	-

Options	
KX-NT505	KX-DT590
Add-on 48-Key Module	Digital DSS console (48-Key)

IP Conference Phone	
KX-NT700	
	<ul style="list-style-type: none"> <li>• Full duplex acoustic echo-canceller</li> <li>• Conference recording with SD Memory Card</li> <li>• Power over Ethernet (PoE)</li> <li>• Speech speed conversion</li> <li>• Conference phone manager application</li> </ul>
Compatible with Panasonic NS, NCP, TDE Series	

Note:

- The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Panasonic Corporation is under licence.
- Some models are available in limited regions. Please contact your Panasonic sales person to confirm the availability of specific models in your country.
- Design and specifications are subject to change without notice.



	SIP Phones					
	KX-UT670	KX-UT248	KX-UT136	KX-UT133	KX-UT123	KX-UT113
Main LCD Display (Lines/Characters)	7 inch colour touch display	6 / 24	6 / 24	3 / 24	3 / 24	3 / 24
LCD Backlight	Yes	Yes	Yes	Yes	Yes	-
Flexible CO Keys	4 x 6	3 x 8	24	24	-	-
Self-Labeling	Yes	Yes	-	-	-	-
Navigator Keys	-	Yes	Yes	Yes	Yes	Yes
Soft Keys	- (Touch Panel)	4	4	4	4	4
Call Log Incoming/Outgoing Calls	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes
Auto Redial	-	-	-	-	-	-
Ethernet Port	2-Port (GbE)	2-Port (GbE)	2-Port	2-Port	2-Port	1-Port
Power over Ethernet (PoE)	Yes	Yes	Yes	Yes	Yes	Yes
AC Adaptor	Option	Option	Option	Option	Option	Option
SIP Accounts	6	6	4	4	2	2
IP Version	IPv4	IPv4	IPv4	IPv4	IPv4	IPv4
DHCP Client	Yes	Yes	Yes	Yes	Yes	Yes
DNS	Yes	Yes	Yes	Yes	Yes	Yes
HTTP	Yes	Yes	Yes	Yes	Yes	Yes
HTTPS	Yes	Yes	Yes	Yes	Yes	Yes
SNTP Client	Yes	Yes	Yes	Yes	Yes	Yes
VLAN (802.1q)	Yes	Yes	Yes	Yes	Yes	Yes
Eco Mode	-	Yes	Yes	Yes	Yes	Yes
Speakerphone	Yes (Full Duplex)	Yes (Full Duplex)	Yes	Yes	Yes	Yes
Headset Port	Yes	Yes	Yes	Yes	Yes	Yes
Electric Hook Switch (EHS)	Yes	Yes	Yes	Yes	-	-
Built-in Bluetooth®	-	Yes	-	-	-	-
Network Camera Monitoring	Yes	-	-	-	-	-
Application Development	Yes	-	-	-	-	-
Wall Mountable	Option	Option	Option	Option	Option	Option



	DECT Wireless System Portable Station		
	Tough Model	Slim and Light Model	Standard Model
	KX-TCA385	KX-TCA285	KX-TCA185
Main LCD Display	1.8 inch colour LCD	1.8 inch colour LCD	1.8 inch colour LCD
LED	Ringer/Charge	Ringer/Charge	Ringer/Charge
Handset Phonebook (PBX)	Up to 500 Numbers	Up to 500 Numbers	Up to 500 Numbers
Call Log Incoming/Outgoing Calls (PBX)	10 / 5	10 / 5	10 / 5
Flexible CO Keys	12	12	12
Soft Keys	3	3	3
Redial	Yes	Yes	Yes
Message Waiting Indication	Yes	Yes	Yes
3-Party Conference	Yes	Yes	Yes
DECT Paging	Yes	Yes	Yes
Built-in Bluetooth®	Yes	Yes	-
Phonebook Transfer via Bluetooth®	Yes (vCard V2.1)	Yes (vCard V2.1)	-
Noise Reduction	Yes	Yes	Yes
Splash and Dust Resistant	IP65 <sup>*1</sup>	-	-
Speakerphone (Full Duplex)	Yes	Yes	Yes
Headset Port	-	Yes	Yes
Vibrate Ring	Yes	Yes	Yes
Battery Talk/Standby Time <sup>*2</sup>	Up to 13 hours/ Up to 200 hours	Up to 13 hours/ Up to 200 hours	Up to 11 hours/ Up to 200 hours
Battery Charge Time	3 hours	3 hours	7 hours
Battery Type	Li-ion battery pack x 1	Li-ion battery pack x 1	Ni-MH AAA battery x 2
Belt Clip	Yes (Clip type)	Yes (Swivel type)	Yes (Swivel type)
Dimensions (W x D x H) (mm)	55 x 23 x 151.5	48.5 x 17.9 x 127.5	48.2 x 25.4 x 146.3
Weight (g)	150 (Belt clip is included)	88	115

\*1 IP65 compliant: Protection against water jets projected from a nozzle from any direction and protection against dust entering the handset.  
\*2 Operating time may be shorter than listed above depending on usage conditions and ambient temperature.

## IP Cell Station



**KX-NCP0158**  
LAN I/F  
8ch speech paths

## Cell Station



**KX-TDA0155**  
DPT I/F  
2ch speech paths  
**KX-TDA0156**  
CS I/F  
4ch speech paths

## Repeater



**KX-A405**  
A repeater can be used to extend the range.